

***GO ANYWHERE***



***2022***



ARGO can go where others can't.  
Designed and built to go anywhere.  
Any peak. Any valley.  
Any obstacle in between.  
Land.

Water.

All surfaces on Earth.

The all-new '22 ARGO models  
are ready to take on  
whatever you throw at them.

XTVs. ATVs. SXSs. UTVs.

Our growing family of vehicles is tailored  
around your needs to master the wrath  
of Mother Nature or explore her beauty.

This is done with purpose.

Our powerful approach  
to powersports is quite simple.

Know no boundaries.

Innovate. Challenge. Outsmart.

Follow no one.

ARGO continues to deliver vehicles  
that are second to none and a lineup  
that's bigger and better than ever.

Now load up your trailer.

Get the heck out of Dodge.

And go experience how  
ARGO is One With Nature.

# *ONE WITH NATURE*



# XTVs

**MAGIC WITHOUT THE TRICKS.**

Look around. This is what you call magical. When you have an amphibious ARGO XTV, you have the power to discover amazing places typically seen in coffee table books or through a drone viewfinder. Whether you're going on a weekend hunting trip, working overtime on a job site or escaping to clear out the cobwebs — the magic starts to happen in unexpected ways when people and machines are one with nature.



## UPPING THE ANTE IN ENTRY-LEVEL.

The Frontier six-wheeled amphibious vehicle is the starting point for our XTV lineup — a point that demonstrates the high standards at ARGO. All of our 6x6 XTVs deliver the same dependable power and reliability of their bigger siblings to maximize your ability in the woods, mud or water. Our classic transmission with ARGO Progressive Steering (APS) and the addition of the all-new Instant Torque Clutch (ITC) provide smooth handling for both new and seasoned outdoor enthusiasts. Feel in control, safe and excited at all times. The new '22 Frontier 6x6 Series continues to rise above the industry's standard definition of entry-level.



### FRONTIER KEY FEATURES


- 650 Series (23HP Carb) or 700 Series (23HP EFI) V-Twin Engine
- Classic Transmission
- ARGO Progressive Steering (APS)
- New Instant Torque Clutch (ITC)
- New Quieter Muffler
- 24" Tires
- 8" Steel Offset Rims
- Rear Side Seats
- Front Flat Floor
- New 8.5 gal Steel Fuel Tank
- New Fuel Level Display on Deluxe Gauge
- Single Low Projector Beam Headlights
- New Hi-Vis LED Brake/Taillights
- HDPE Body Plastics



ARGO Progressive Steering (APS)



Deluxe Gauge with 11 Functions



Flat Front Floor



FRONTIER 650 6X6



FRONTIER 700 6X6



FRONTIER 700 SCOUT 6X6



## HORSEPOWER MOVES YOU IN MORE WAYS THAN ONE.

There's nothing quite like a change of scenery, especially if that change is set somewhere way back in the middle of nowhere. The amphibious Frontier 8x8 Series helps hunters reach trophy-buck hiding spots, anglers find hard-to-reach honey holes and outdoor newcomers locate areas they never knew existed. "Hey, look at that!" This year's lineup includes a model, engine and price point that zeros in on your specific needs, with features far from ordinary. It's time you create more real-life adventures to drive your affinity for dirt, rocks, mud, water, trees, bugs, wildlife and nature for years to come.




### FRONTIER KEY FEATURES

- 650 Series (23HP Carb) or 700 Series (23HP EFI) V-Twin Engine
- Classic Transmission
- ARGO Progressive Steering (APS)
- New Instant Torque Clutch (ITC)
- New Quieter Muffler
- 24" Tires
- 8" Steel Offset Rims
- Rear Side Seats
- Front Flat Floor
- New 8.5 gal Steel Fuel Tank
- New Fuel Level Display on Deluxe Gauge
- Single Low Projector Beam Headlights
- New Hi-Vis LED Brake/Taillights
- HDPE Body Plastics



23 HP V-Twin Engine



Rear Side Seats



New Hi-Vis LED Brake/Taillights



FRONTIER 650 8X8



FRONTIER 700 8X8



FRONTIER 700 SCOUT 8X8



## MOUNT UP. THIS CAVALRY IS READY TO ROLL.

Sound the trumpet. This new lineup is raring to go on its next adventure. The amphibious Aurora 8x8 Series is the premium platform for ARGO, making it the most advanced and powerful XTV available. The massive V-Twin engine options give you the high-performance power to conquer obstacles at work or at play. The new Instant Torque Clutch (ITC) technology complements the Admiral transmission with ARGO Progressive Steering for a smooth and comfortable ride. This modern-day cavalry of land-and-water warriors is ready to take on nature's toughest battles. Charge!



### AURORA KEY FEATURES

- 800 Series (30 HP EFI), 850 Series (33HP EFI) or 950 Series (40HP EFI) V-Twin Engine
- Admiral Transmission with Triple Differential
- ARGO Progressive Steering (APS)
- New Instant Torque Clutch (ITC)
- 25" Tires
- 9" AirLock™ Steel Rims
- Rear Bench or Side Seats
- Front & Rear Flat Floor with Rubber Mats
- New 8.5 gal Steel Fuel Tank
- New Fuel Level Display on Deluxe Gauge
- Dual Hi/Low Projector Beam Headlights
- Hi-Vis LED Taillights
- Heat-Reflective Firewall
- Premium HDPE Body Plastics



ARGO Progressive Steering (APS)



New Instant Torque Clutch (ITC)



Hi-Vis LED Taillights



AURORA 800/850 SX 8X8

AURORA 950 SX 8X8

AURORA 800/850/950 SX HUNTMASTER 8X8

AURORA 950 BIGFOOT MX8

AURORA 800/850 SX-R 8X8

AURORA 950 SX-R 8X8



## AIM, SIGHT AND SLOWLY SQUEEZE THE TRIGGER.

Bang! The long-awaited single shot defines your hunting prowess. We're all big-game hunters for the experience, thrill and opportunity to share our stories over and over and over again. Camp operators, lodge owners and big-game guides understand it takes much more than a firearm. The Conquest Outfitter has been the preferred pack mule to get back to those spots only our feathered friends know about. With a dependable 800 V-Twin EFI liquid-cooled or 950 V-Twin EFI fan-cooled engine, you can be sure nothing will stop you, including high altitudes. Make sure the Conquest Outfitter is at your hunting camp if you want something mounted on your wall.




### CONQUEST OUTFITTER KEY FEATURES

- 800 Series (30HP EFI L/C) or 950 Series (40HP EFI F/C) V-Twin Engine
- Admiral Transmission with Triple Differential
- New Instant Torque Clutch (ITC)
- 25" Tires
- 9" AirLock™ Steel Rims
- Rear Side Seats
- Front Flat Floor
- New 8.5 gal Steel Fuel Tank
- Dual Hi/Low Projector Beam Headlights
- Auto Chain Lubrication
- Oil Bath Axles
- Brushguard with 4,500 lb Winch
- Heavy-Duty Front Rack
- Premium HDPE Body Plastics



Premium 17 Functional Gauge



Heavy-Duty Front Rack and 4500 lb Winch



New TrueTimber® Prairie Camo



CONQUEST 800 OUTFITTER 8X8



CONQUEST 950 OUTFITTER 8X8



## COMMANDING POWER GETS HIGH RANK.

The world's enduring amphibious Xtreme Terrain Vehicle (XTV) gives you a rare combination of reliable horsepower, advanced technology and high-quality comfort. You can't find anything on Earth that compares to an ARGO XTV. Nobody builds this type of extreme vehicle. That's because we have a 55-year-plus head start on proprietary technology that pushes the boundaries to seamlessly become one with nature.

### BIG AND SMALL BLOCK ENGINES

High-performance 4-cycle, twin-cylinder, OHV, low-vibration engines deliver clean, dependable power for your ARGO.

- 650 Series 23HP V-Twin Fan Cooled
- 700 Series 23HP V-Twin EFI Fan Cooled
- 800 Series 30HP V-Twin EFI Liquid Cooled
- 850 Series 33HP V-Twin EFI Fan Cooled
- 950 Series 40HP V-Twin EFI Fan Cooled



### 800 SERIES ENGINE

Specifically designed for commercial application. This liquid-cooled engine provides the perfect balance of horsepower and torque for the Aurora & Conquest Series.



### 650 AND 700 SERIES ENGINES

The Small Block V-Twin engines are design-engineered to handle the most demanding terrain. Energetic and quick-starting, these powerhouse engines feature a number of advanced technologies and integrated components but remain lighter and compact.



### 850 AND 950 SERIES ENGINES

Legendary. Respected. Proven. These dependable 4-stroke Big Block™ V-Twin engines are built to never let you down. Our highest horsepower series, these engines also deliver the highest torque available in an ARGO XTV.

### CONQUEST SERIES



### ADMIRAL

The Admiral transmission uses complex gearing, including dual differentials on the output shafts. When the driver is steering, the braking force is not applied to the output shafts but to a steering differential, which translates to a vastly different driving experience.

While the driver is steering in high gear, the output shafts rotate at a 3:1 ratio, yielding smoother, gentler steering. Although there's no ability for zero turn in high range, selecting low range enables operation similar to a traditional skid steer vehicle offering a zero-radius turn.

### AURORA SERIES



### ADMIRAL with APS

The Admiral with ARGO Progressive Steering (APS) is an innovation in braking force application to the transmission steering differential. By adding a spring element between the handlebars and the brake system, we have achieved a progressive dual-rate steering system.

This development, combined with the Admiral transmission, is a technological milestone that gives the ultimate driver experience. Steering events are effortless and confidence inspiring, offering the smoothest turning available in an ARGO XTV. An ARGO is as fun and comfortable to drive as any UTV.

### FRONTIER SERIES




### CLASSIC with APS

The Classic transmission is our simplest design and operates like a mechanical skid steer, which gives it incredible maneuverability. In order to provide vehicle steering, braking force is applied directly to the output of the appropriate side of the transmission based on operator steering input. In both high and low range, the Classic transmission provides zero-radius turns to get you in and around extreme terrain.

ARGO Progressive Steering (APS) with the Classic transmission achieves a smooth and comfortable drive experience to all XTVs in the Frontier Series. Geared by ODG.

### NEW DRIVE TECHNOLOGY.

The new ARGO Instant Torque Drive System (ITDS) dramatically improves low-end torque and increases acceleration. The new Instant Torque Clutch (ITC) is designed to provide the optimal gear ratio shifting seamlessly throughout the full range to utilize the massive torque and power of our engines.



Coupling the new Instant Torque Clutch (ITC) with our Admiral or Classic transmission will increase the torque by 28% compared to our previous clutches with a High Torque (HT) transmission and will increase acceleration by 25% compared to our previous clutches with a Standard Torque (ST) transmission, providing you with increased torque and acceleration into one package.



## ARGO PROGRESSIVE STEERING (APS).

APS has innovated brake force application to the transmission steering differential. The brakes are an integral part of steering an ARGO. To remove the traditional skid steering jerkiness, we added a spring element between the handlebars and the brake system to achieve a progressive dual-rate steering system. The result is ARGO Progressive Steering (APS).

APS, combined with the Admiral and Classic transmissions, is a technological milestone for ARGO that delivers the ultimate driver experience. Steering is effortless, and APS provides confidence-inspiring handling for all riders. This offers improved controllability and the smoothest turning available in an ARGO XTV. It's in a class of its own.

## SILKY-SMOOTH CORNERING AND SKID-STEERING CAPABILITY FOR TIGHT SPOTS.


APS makes the ARGO XTV as fun and comfortable to drive as any UTV.



By adding a spring element between the handlebars and the brake system, we achieved a progressive dual-rate steering system.



Steering is now effortless with an increase of a 4-times-wider range of steering motion, offering the smoothest turning available in an ARGO XTV.



— ARGO PROGRESSIVE STEERING  
 - - - TRADITIONAL SKID STEERING

## SUSPENSION SYSTEM.

Newcomers can't believe there isn't a traditional suspension system on our XTVs. Riding an ARGO is smooth and comfortable because of one-of-a-kind tires and rims. These tires can absorb all the shock of extreme terrains with ease.



### LOW-PRESSURE TIRES

ARGO tires are custom engineered to provide propulsion for the vehicle when used amphibiously or to provide superior traction when off-roading in challenging terrain.



### AIRLOCK™ RIMS

Our signature AirLock™ steel rims. These premium rims allow operators to adjust tire pressure to the terrain. The AirLock™ feature keeps the tire firmly fixed to the rim in rugged terrain while providing a 30% smoother ride.



### RUBBER TRACKS

ARGO heavy-duty rubber tracks provide optimum flotation over snow or swamp with minimal ground pressure. Provides exceptional traction, is lightweight and has low-rolling resistance. Easily installs around the tires.



### AMPHIBIOUS BODY

The one-piece lower body is the signature ARGO design feature. Its smooth, durable underbody floats over potential snags, stumps and outcrops, as well as swamps and water.



### REDUCED UNDERHOOD TEMPERATURE

To ensure comfort for the operator and passengers, heat-reflective and absorptive material is integrated into the firewall. A composite exhaust shroud goes one step further and effectively redirects heat while producing a subtle note from the exhaust.



## CUSTOMIZE YOUR XTV JUST THE WAY YOU LIKE IT.

You can build your perfect XTV for wherever you ride with high-quality tracks, trailers and more. Visit your dealer or [ARGOxtv.com](http://ARGOxtv.com) to view our full lineup of genuine ARGO accessories.

- 1 Tracks** – From extreme-duty to general-purpose, ARGO heavy-duty rubber and medium-duty plastic tracks are designed to give your ARGO XTV more traction for the most challenging terrain. Durable construction ensures a smooth ride.
- 2 Trailers** – Gear up an ARGO amphibious trailer with all of your power tools, equipment and outdoor gear. You'll have plenty of room to haul your precious cargo no matter the destination or terrain. Available in four- or eight-wheel models.
- 3 Tops** – Make sure you keep yourself covered from sun, rain or snow with our hardtops or convertible tops. These tops provide additional safety and coverage for your cargo from whatever Mother Nature throws at you.
- 4 Outboard Motor Mount** – Add a little more speed on the water by attaching an outboard motor to your ARGO. A genuine ARGO high-quality mounting bracket makes outboard installation quick and easy.
- 5 Windshield** – Scratch-resistant acrylic means your windshield can take a beating out in the wild. Fold-over hinge for storage and a mounting location for optional windshield wiper accessory make installation quick and easy.
- 6 ROPS** – For unpredictable and extreme terrain, add additional protection for your ARGO Aurora or Conquest models. Roll-Over Protective Structure (ROPS) provides additional peace of mind when the terrain gets hairy.
- 7 Steel Rack** – Organize all of your hunting and outdoor gear with our steel rack. Gain additional stowage for packs and equipment for long hunting trips or weekend excursions.
- 8 Blade** – Maximize the utilization of your ARGO XTV for snow or dirt. This high-quality 80"-wide steel blade features multi-angle positions. Requires the power winch for raise-and-lower operation.





# ATVs

***GETTING LOST HELPS FIND A NEW PERSPECTIVE.***

Nature is powerful and exerts an undeniable effect on ATV riders no matter where they ride. Miles of sun-drenched trail riding can energize just about anyone. Its nurturing effect calms and inspires you. Riding an ARGO ATV will get you to appreciate what a vehicle like this can do from sunrise to sundown, like recharging your personal battery. When you hit the trail to explore new territories, you're bound to unearth a newfound point of view.




## SAFETY AND FUN TETHERED TOGETHER.

Introducing the all-new Xplorer XC 90 youth ATV. This model is engineered for kids 12 years of age and up to provide lifelong memories. The XC 90 has many safety features straight from the factory, including an adjustable throttle for limiting speed and a handlebar tether cord adults can pull as a remote shut-off switch to stop the 89cc fan-cooled engine. This is the perfect youth platform to teach the fundamentals of riding and to learn the rules of nature's endless playground.



### XPLORER XC 90 KEY FEATURES

- 89cc Fan-Cooled Carbureted Engine
- Automatic CVT
- Electric Start with Kickstart Back-Up Option
- Chain Drive
- Steel Rims
- 2WD
- F/N/R Gear Selection
- Independent Single A-Arm Suspension with Dual Drum Brakes in the Front
- Swing Arm Suspension with Hydraulic Disc Brake in the Rear
- Single Hi/Low Beam Headlight
- Rear Taillight & Brake Light
- Highly Visible Orange Whip Flag
- Tether Cord



XPLORER XC 90



## ON A MISSION SINCE DAY ONE.

The ARGO team has been on a mission since debuting the ARGO Xplorer XR Series five short years ago to offer a better ATV, period. Better horsepower. Better suspension. Better comfort. Better, well, you get it. The all-new '22 XR 500 Series adds a fresh laundry list of enhancements, including the new 443cc liquid-cooled engine with EFI, new performance clutching and class-leading suspension. We don't subtract essential features, like engine braking, to save a few bucks; we make everything better. Go see why an ARGO XR 500 Series is a better fit for you.



### XPLORER XR 500 KEY FEATURES


- New 443cc Liquid-Cooled Engine w/ EFI
- Automatic CVT with Engine Braking
- 24" Kenda Tires with Steel Rims
- Push-Button 2WD/4WD with Front Differential Lock
- Front & Rear Independent Double A-Arm Suspension
- Front & Rear Hydraulic Disc Brakes
- Heavy-Duty Steel Front and Rear Racks
- Deluxe Digital Gauge
- Dual Hi/Low Beam Headlights with Taillights
- 2" Receiver

#### SE Models Add:

- 24" Kenda Tires with Aluminum Rims
- 3,000 lb Winch
- Premium Painted Plastic Body Panels



New 443cc Liquid-Cooled Engine with EFI



Push-Button 2WD/4WD with Front Differential Lock



Digital Gauge



XPLORER XR 500



XPLORER XR 500 SE



## THE MUDDY STANDARD. CLEANED UP AND POLISHED.

ARGO believes the standard of ATVs needs to be shifted in a direction driven by quality. Every trail will throw you a curveball, which is why ARGO delivers the best in high performance — rain or shine. The all-new XR 700 Series applies the hard brake on the industry's substandard factory features to offer you more — new power, improved suspension, superior ergonomics and plenty of capacity straight from the factory. This belief in a higher standard is a true testament of our strong commitment to improve your experience, regardless if you're working hard or playing even harder.




### XPLORER XR 700 EPS KEY FEATURES


- New 695cc Liquid-Cooled Engine with EFI
- Automatic CVT with Engine Braking
- 25" Maxxis Tires with Steel Rims
- Electric Power Steering (EPS)
- Stainless Steel Muffler
- Push-Button 2WD/4WD with Front Differential Lock
- Front & Rear Double A-Arm Suspension with Sway Bar
- Front & Rear Hydraulic Disc Brakes
- Heavy-Duty Steel Front & Rear Racks
- Premium Gauge
- Lockable Front and Center Console

### LE Models Add:


- 26" Maxxis Tires with Aluminum Rims
- Handguards
- 3,000 lb Winch
- Premium Painted Plastic Body Panels



Heavy-Duty Steel Front & Rear Racks



Push-Button 2wd/4wd with Front Differential Lock



Premium Gauge



XPLORER XR 700 EPS



XPLORER XR 700 LE



## THE BACKSEAT DRIVER WANTS TO DRIVE.

Being behind the handlebars is the thrill we all can't get enough of on the trail. You're in control of your picturesque journey turn after turn. There's nothing quite like it. With the new 2022 Xplorer XRT 2-Ups, passengers will now want some time up front. The 561cc or 997cc liquid-cooled engines are big reasons why the passenger will say, "Pull over, it's my turn!" Passengers want to experience premium off-road performance and control for themselves. You can't blame them.



### XPLORER XRT KEY FEATURES


- 561cc or 997cc Liquid-Cooled Engine with EFI
- Automatic CVT with Engine Braking
- 25" Kenda Tires with Steel Rims
- Push-Button 2WD/4WD with Front Differential Lock
- Push-Button Locking/Unlocking Rear Differential
- Front & Rear Independent Double A-Arm Suspension
- Front & Rear Hydraulic Disc Brakes
- Heavy-Duty Steel Front & Rear Racks
- Premium Gauge
- Dual Hi/Low Beam Headlights and Taillights

### LE Models Add:


- 26" Maxxis Tires with Aluminum Rims
- Electric Power Steering (EPS)
- Front Bumper (*XRT 1000 LE only*)
- Front Brushguard (*XRT 570 LE only*)
- 3,000 lb Winch
- Eyebrow Lights
- Premium Painted Plastic Body Panels
- Handguards (*XRT 1000 LE model only*)



Deluxe 2-Up Seating and Footrest



Heavy-Duty Steel Rear Rack with Integrated Passenger Back Rest



Push-Button Locking/Unlocking Front & Rear Differential



XPLORER XRT 570



XPLORER XRT 570 LE



XPLORER XRT 1000 LE



**THE DISTINCTION IS IN THE DETAILS.**

Constant improvement is a must with every detail in our ATVs. Our engineers are avid ATV riders too, and are committed to delivering a high-quality experience.



**XR 500 SERIES ENGINE**

This compact 4-stroke single overhead camshaft (SOHC) engine is liquid cooled and features electronic fuel injection (EFI). Offering the perfect balance of horsepower and torque, the 443cc engine will work just as hard as you do to get the job done while providing the necessary power for trail rides.

**XR 700 SERIES ENGINE**

The mighty 695cc liquid-cooled 4-stroke engine comes standard with EFI and four valve configurations. Sporting commendable fuel economy, this engine provides users with enough horsepower and torque for versatile applications. The all-new XR 700 will enhance your confidence when motoring through the powerband.



**XRT 570 ENGINE**

The 561cc single-cylinder EFI engine with SOHC positions itself as a versatile engine packing enough power for both work and play. This reliable four-stroke engine with four-valve technology and liquid and oil cooling with two separate radiators is equipped with EFI to deliver outstanding fuel efficiency, cleaner exhaust emissions and a precise throttle response regardless of changes in elevation or temperature.

**XRT 1000 ENGINE**

The dynamic 997cc V-Twin SOHC 4-stroke engine comes with EFI and liquid cooling for optimal performance in all conditions. With a subtle roar, it's designed and tuned to deliver superlative fuel economy and progressive torque over its broad powerband, with an auxiliary fan for consistent performance in the most demanding conditions.



**HEAVY-DUTY STEEL RACKS**

Gear up and let's go. Industry-best heavy-duty steel front and rear racks deliver 115-210 pounds carrying capacity, with multiple tie-down locations for maximum versatility.



**PUSH-BUTTON 2WD/4WD WITH FRONT DIFFERENTIAL LOCK**

With just a push of a button, selecting between 2WD/4WD gives you on-demand capabilities with the addition of a locking front differential for added grab and traction in unruly terrain.



**3,000 LB WINCH**

When you need extra muscle, this heavy-duty 3,000 lb. winch has been engineered for durability, which maximizes strength and longevity. (SE and LE models only)



**PREMIUM GAUGE**

Ride efficiently and safely. Digital instrument panel includes odometer, speedometer, tripmeter, RPM, transmission position, 2WD/4WD/ lock indicator, fuel gauge, temperature and low-battery, high-beam and check-engine lights.



**MAXXIS OFF-ROAD TIRES**

Control and handling for every turn and trail. The Maxxis tires have an aggressive off-road design providing superior traction when venturing off road. (XR 700 LE, XRT 570 LE and XRT 1000 LE models only)



# SXS

***TO GROW, ADD DIRT, WATER AND GRIT.***

To out-innovate the leaderboard, we're building upon our seasoned team of engineers and impressive pedigree in the powersports industry. When we *Know No Boundaries*, opportunities and excitement push us to achieve the impossible. We're proud to introduce another member of the ARGO family: the all-new side-by-side Magnum Series. Experience how a new ARGO SXS works and plays with nature seamlessly.



**TESTED TO OVERCOME OBSTACLES.  
ESPECIALLY BRAND LOYALTY.**

Brand loyalty is hard to beat. That's why ARGO put its best foot forward out of the gate with the all-new Magnum Series Side-by-Side. The new Magnum XF 500 or XF 500 LE is built for superior on- and off-trail performance and takes quality to a whole new level — a level that will impress guys like Uncle Frank. Our SxS debut features a dependable 443cc liquid-cooled 4-stroke EFI engine, push-button 2WD/4WD with front differential lock, and impressive ergonomics for both riders. Inch by inch, mile by mile, dollar for dollar, the new Magnum Series has been tested in the field and on the trail to give the confidence you'll need to park an ARGO SxS with your other toys.



**MAGNUM XF 500 KEY FEATURES**

- 443cc Liquid-Cooled Engine with EFI
- Automatic CVT with Engine Braking
- 25" Maxxis Tires with Steel Rims
- Front & Rear Independent Double A-Arm Suspension
- Push-Button 2WD/4WD with Front Differential Lock
- Front & Rear Hydraulic Disc Brakes
- 1,200 lb (544 kg) Towing Capacity with 2" Receiver
- Rear Dump Box with Rubber Bed Mat
- Adjustable Tilt Steering Wheel
- Fits in Full-Size Truck Bed
- Featuring Turfsaver™ for Tight Radius Turning

**LE Models Add:**


- Duro Power Grip 25" Tires with Aluminum Rims
- Electric Power Steering (EPS)
- 3,000 lb Winch
- Premium Painted Plastics Body Panels



*Some models shown with accessories.*



Rear Dump Box with Bed Mat



Front & Rear Independent Double A-Arm Suspension



Adjustable Tilt Steering Wheel



MAGNUM XF 500



MAGNUM XF 500 LE



# ***PRO SERIES***

***FOUR SEASONS. ONE FORCE OF NATURE.***

Bold, brave and driven to tackle any job site, project or critical mission, ARGO Commercial XTVs and UTVs were born to run wild — far away from urban jungles and strip malls. When you work with Mother Nature, she seems to greet you with a welcome mat or a wrestling mat. You just never know. It all comes down to being prepared for anything. There's no doubt the ARGO Commercial Series lineup is a force of nature.

Some may say, "freaks of nature."



## DEPENDABILITY. YOU CAN COUNT ON IT.

The call just came in. Time is of the essence. The Aurora Responder XTV is designed to safely perform in emergency situations. From broken legs on the slopes to broken hearts in natural disasters, the reliable 850 V-Twin engine gives you the power and rugged stability with its built-in stretcher mount to achieve successful rescues. At ARGO, we'd like to thank the heroic men and women who risk their lives every day to save others and we're proud to support their bravery.




### AURORA RESPONDER KEY FEATURES


- 850 Series (33HP EFI) V-Twin Engine
- Admiral Transmission with Triple Differential
- ARGO Progressive Steering (APS)
- New Instant Torque Clutch (ITC)
- 25" Tires
- 9" AirLock™ Steel Rims
- Rear Bench or Side Seats
- Front & Rear Flat Floor with Rubber Mats
- New 8.5 gal Steel Fuel Tank
- New Fuel Level Display on Premium Gauge
- Dual Hi/Low Projector Beam Headlights
- Hi-Vis LED Taillights
- Stretcher Mount
- Roll-Over Protection Structure (ROPS)
- Heat-Reflective Firewall
- Premium HDPE Body Plastics



Stretcher Mount



Split Seats



Front and Rear Flat Floors



AURORA 850 SX RESPONDER 8X8



AURORA 850 SX-R RESPONDER 8X8



# DON'T WASTE NATURAL RESOURCES.

The job has to get done. No excuses. Nature will have its way with you unless you come prepared. Swamps, water, mud, rocks, snow, ice, logs and ravines will make your job very challenging. The unstoppable power of ARGO Conquest Pro Series removes the guessing game about getting to your job site or not. Protect your natural resources like time and personal energy by dominating unknown pitfalls. And when you do, you'll save precious daylight hours, money and your sanity.




### CONQUEST PRO KEY FEATURES

- 800 Series (30HP EFI L/C) or 950 Series (40HP EFI F/C) V-Twin Engine
- 50 or 60 AMP Max Output Alternator
- Admiral Transmission with Triple Differential
- New Instant Torque Clutch (ITC)
- New Quieter Muffler
- 25" Tires
- 9" AirLock™ Steel Rims
- Flat Front Floor
- New 8.5 gal Steel Fuel Tank
- New Fuel Level Display on Premium Gauge
- Dual Hi/Low Projector Beam Headlights
- Auto Chain Lubrication
- Oil Bath Hubs
- Roll-Over Protection Structure (ROPS)
- Brushguard with 4,500 lb Winch
- Premium HDPE Body Plastics



25" Tires on AirLock Steel Rims



Roll-Over Protection Structure (ROPS) with Solid Roof Panel and Windshield (XT-X and XT-L Models)



4,500 lb Winch



CONQUEST PRO 800/950 XT



CONQUEST PRO 800/950 XT-L



CONQUEST PRO 800/950 XT-X



## EYES WIDE OPEN.

You won't believe it. There's no question the physical presence of the ARGO Sherp Series is remarkable, but what these amphibious utility task vehicles (UTVs) can accomplish is unbelievable. ARGO Sherp Series is designed to maneuver effortlessly on any surface with its smooth skid steering, unique suspension and massive tubeless ultra-low-pressure tires. These lightweight UTVs give you big performance with as little impact as possible. Inside the ARGO Sherp Series is where technology, comfort and safety team up. Innovative features inside and out give the ARGO Sherp Pro XT, ARK XTX and XTZ the ability to get your gear, cargo and teams anywhere on Earth.



### ARGO Sherp PRO XT KEY FEATURES

- Eco-Friendly Doosan® D18 Diesel Engine
- Smooth Skid Steering
- Adjustable Pneumatic Circulating Tires
- 71" Tubeless Ultra-Low-Pressure Tires
- High-Pressure Fuel Injection
- Wheel Canister Fuel Tanks
- Enclosed Final Drive Chain, Oil Bath Lubricated
- Back-Up Camera with Alarm
- LED Hi/Low Beam Headlights
- Loading Capacity 2,645 lb
- Three-Point Safety Seat Belts
- Up to 8 Passengers with Optional Seats



### ARGO SHERP ARK XTX & XTZ KEY FEATURES

- Eco-friendly Doosan D24 Diesel Engine
- Multi-Power Articulated Steering
- Adjustable Pneumatic Circulating Tires
- 63" Tubeless Ultra-Low-Pressure Tires
- Wheel Canister Fuel Tanks
- Enclosed Final Drive Chain, Oil Bath Lubricated
- Back-Up Camera with Alarm
- LED Hi/Low Beam Headlights
- Load Capacity: 7,500 lb Total (XTX) and 4,409 lb Total (XTZ)
- Three-Point Safety Seat Belts
- Digital Inclinometer for Critical Tilt Angles
- Up to 4 Passengers XTX
- Up to 22 Passengers XTZ, 4 in the front and 18 in the rear



Doosan Diesel Engines Are Powerful, Reliable and Fuel Efficient with Low Noise and Vibration



Hydraulic Skid Steering Provides Superior Maneuverability



Impressive Strength and Durability with Ultra-Low-Pressure Tires



ARGO Sherp PRO XT



ARGO Sherp ARK XTX



ARGO Sherp ARK XTZ

### COMMERCIAL APPLICATIONS:

- Utilities & Power Lines
- Oil & Gas
- Search & Rescue
- Drilling & Pipeline
- Mining & Exploration
- Government
- Forestry
- Humanitarian
- Construction
- Thrill Seekers



## FRONTIER SERIES SPECS



### FRONTIER 650 6X6

HORSEPOWER	23HP
CYLINDER	V-TWIN
FUEL SYSTEM	CARBURETOR
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	20 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	N/A
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	CLASSIC W/APS
DRIVE BELT	STANDARD
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	ACCESSORY
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	N/A
STRETCHER FRAME	N/A
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	595 lb (270 kg)
LOAD CAPACITY - WATER	395 lb (179 kg)
TOWING CAPACITY	1,200 lb (544 kg)
SEATING CAPACITY - LAND	4
SEATING CAPACITY - WATER	2
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	22 mph (35 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	945 lb (428 kg)
LENGTH (includes winch when standard)	96 in (2,439 mm)
WIDTH	58 in (1,473 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	N/A
ENTRY STEP	ACCESSORY
TIRES	ARGO XT115 24X10-8
RIMS	STEEL OFFSET
GROUND PRESSURE (18" RUBBER TRACKS)	0.73 psi (5 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	GREEN, BLACK, ORANGE



### FRONTIER 700 6X6

HORSEPOWER	23HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	16 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	N/A
BRAKE COOLING FAN	STANDARD
TRANSMISSION	CLASSIC W/APS
DRIVE BELT	STANDARD
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	ACCESSORY
FRONT RACK	STANDARD
BILGE PUMP	STANDARD
ROPS	N/A
STRETCHER FRAME	N/A
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	570 lb (258 kg)
LOAD CAPACITY - WATER	370 lb (168 kg)
TOWING CAPACITY	1,200 lb (544 kg)
SEATING CAPACITY - LAND	4
SEATING CAPACITY - WATER	2
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	22 mph (35 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	970 lb (440 kg)
LENGTH (includes winch when standard)	96 in (2,439 mm)
WIDTH	58 in (1,473 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT115 24X10-8
RIMS	STEEL OFFSET
GROUND PRESSURE (18" RUBBER TRACKS)	0.73 psi (5 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	GREEN, BLACK, ORANGE



### FRONTIER 700 SCOUT 6X6

HORSEPOWER	23HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	16 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	N/A
BRAKE COOLING FAN	STANDARD
TRANSMISSION	CLASSIC W/APS
DRIVE BELT	STANDARD
FULL SKID PLATE	STANDARD
BRUSHGUARD	STANDARD
WINCH	2,500 LB
FRONT RACK	STANDARD
BILGE PUMP	STANDARD
ROPS	N/A
STRETCHER FRAME	N/A
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	510 lb (231 kg)
LOAD CAPACITY - WATER	310 lb (141 kg)
TOWING CAPACITY	1,200 lb (544 kg)
SEATING CAPACITY - LAND	4
SEATING CAPACITY - WATER	2
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	22 mph (35 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,030 lb (467 kg)
LENGTH (includes winch when standard)	103 in (2,616 mm)
WIDTH	58 in (1,473 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT115 24X10-8
RIMS	STEEL OFFSET
GROUND PRESSURE (18" RUBBER TRACKS)	0.73 psi (5 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	TRUETIMBER PRAIRIE CAMO



### FRONTIER 650 8X8

HORSEPOWER	23HP
CYLINDER	V-TWIN
FUEL SYSTEM	CARBURETOR
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	20 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	STANDARD
TRANSMISSION	CLASSIC W/APS
DRIVE BELT	STANDARD
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	ACCESSORY
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	N/A
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	855 lb (388 kg)
LOAD CAPACITY - WATER	755 lb (342 kg)
TOWING CAPACITY	1,200 lb (544 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	16 mph (26 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,195 lb (542 kg)
LENGTH (includes winch when standard)	119 in (3,023 mm)
WIDTH	58 in (1,473 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	N/A
ENTRY STEP	ACCESSORY
TIRES	ARGO XT115 24X10-8
RIMS	STEEL OFFSET
GROUND PRESSURE (18" RUBBER TRACKS)	0.73 psi (5 kPa)
GROUND CLEARANCE (TIRES)	9 in (228 mm)
GROUND CLEARANCE (TRACKS)	10 in (254 mm)
WARRANTY	1 YEAR
COLORS	GREEN, BLACK, ORANGE



### FRONTIER 700 8X8

HORSEPOWER	23HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	16 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	STANDARD
TRANSMISSION	CLASSIC W/APS
DRIVE BELT	STANDARD
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	ACCESSORY
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	N/A
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	840 lb (381 kg)
LOAD CAPACITY - WATER	740 lb (335 kg)
TOWING CAPACITY	1,200 lb (544 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	16 mph (26 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,210 lb (549 kg)
LENGTH (includes winch when standard)	119 in (3,023 mm)
WIDTH	58 in (1,473 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT115 24X10-8
RIMS	STEEL OFFSET
GROUND PRESSURE (18" RUBBER TRACKS)	0.73 psi (5 kPa)
GROUND CLEARANCE (TIRES)	9 in (228 mm)
GROUND CLEARANCE (TRACKS)	10 in (254 mm)
WARRANTY	1 YEAR
COLORS	GREEN, BLACK, ORANGE



### FRONTIER 700 SCOUT 8X8

HORSEPOWER	23HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	16 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	STANDARD
TRANSMISSION	CLASSIC W/APS
DRIVE BELT	STANDARD
FULL SKID PLATE	STANDARD
BRUSHGUARD	STANDARD
WINCH	2,500 LB
FRONT RACK	STANDARD
BILGE PUMP	STANDARD
ROPS	N/A
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	790 lb (358 kg)
LOAD CAPACITY - WATER	690 lb (313 kg)
TOWING CAPACITY	1,200 lb (544 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	16 mph (26 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,270 lb (576 kg)
LENGTH (includes winch when standard)	126 in (3,200 mm)
WIDTH	58 in (1,473 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT115 24X10-8
RIMS	STEEL OFFSET
GROUND PRESSURE (18" RUBBER TRACKS)	0.73 psi (5 kPa)
GROUND CLEARANCE (TIRES)	9 in (228 mm)
GROUND CLEARANCE (TRACKS)	10 in (254 mm)
WARRANTY	1 YEAR
COLORS	TRUETIMBER PRAIRIE CAMO

## FRONTIER PRO SERIES SPECS



**AURORA SERIES SPECS**



**AURORA 800 SX 8X8**

HORSEPOWER	30HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	LIQUID COOLED
ALTERNATOR OUTPUT (MAX)	40 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	ACCESSORY
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	ACCESSORY
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	1,100 lb (499 kg)
LOAD CAPACITY - WATER	900 lb (409 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	24 mph (39 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,450 lb (657 kg)
LENGTH (includes winch when standard)	119 in (3,023 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT117 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.88 psi (6.1 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	GREEN, BLACK, ORANGE



**AURORA 800 SX HUNTMASTER 8X8**

HORSEPOWER	30HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	LIQUID COOLED
ALTERNATOR OUTPUT (MAX)	40 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	3,500 lb
FRONT RACK	STANDARD
BILGE PUMP	STANDARD
ROPS	ACCESSORY
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	1,000 lb (454 kg)
LOAD CAPACITY - WATER	800 lb (363 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	24 mph (39 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,550 lb (703 kg)
LENGTH (includes winch when standard)	126 in (3,200 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT117 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.88 psi (6.1 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	TRUETIMBER PRAIRIE CAMO



**AURORA 850 SX 8X8**

HORSEPOWER	33HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	ACCESSORY
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	ACCESSORY
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	1,100 lb (499 kg)
LOAD CAPACITY - WATER	900 lb (409 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	24 mph (39 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,450 lb (657 kg)
LENGTH (includes winch when standard)	119 in (3,023 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT117 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.88 psi (6.1 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	GREEN, BLACK, ORANGE



**AURORA 850 SX HUNTMASTER 8X8**

HORSEPOWER	33HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	3,500 lb
FRONT RACK	STANDARD
BILGE PUMP	STANDARD
ROPS	ACCESSORY
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	1,000 lb (454 kg)
LOAD CAPACITY - WATER	800 lb (363 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	24 mph (39 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,550 lb (703 kg)
LENGTH (includes winch when standard)	126 in (3,200 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT117 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.88 psi (6.1 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	TRUETIMBER PRAIRIE CAMO



**AURORA 950 SX 8X8**

HORSEPOWER	40HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	ACCESSORY
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	ACCESSORY
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	1,080 lb (490 kg)
LOAD CAPACITY - WATER	880 lb (400 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	25 mph (40 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,470 lb (668 kg)
LENGTH (includes winch when standard)	119 in (3,023 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT117 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.88 psi (6.1 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	GREEN, BLACK, ORANGE



**AURORA 950 SX HUNTMASTER 8X8**

HORSEPOWER	40HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	3,500 lb
FRONT RACK	STANDARD
BILGE PUMP	STANDARD
ROPS	ACCESSORY
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	1,000 lb (454 kg)
LOAD CAPACITY - WATER	800 lb (363 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	25 mph (40 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,560 lb (708 kg)
LENGTH (includes winch when standard)	126 in (3,200 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT117 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.88 psi (6.1 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	TRUETIMBER PRAIRIE CAMO



## AURORA SERIES SPECS



### AURORA 800 SX-R 8X8

HORSEPOWER	30 HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	LIQUID COOLED
ALTERNATOR OUTPUT (MAX)	40 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	ACCESSORY
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	STANDARD
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	870 lb (395 kg)
LOAD CAPACITY - WATER	670 lb (304 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	4
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	24 mph (39 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,680 lb (762 kg)
LENGTH (includes winch when standard)	119 in (3,023 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	77 in (1,956 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT117 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.88 psi (6.1 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	GREEN, BLACK, ORANGE

### AURORA 850 SX-R 8X8

HORSEPOWER	33HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	ACCESSORY
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	STANDARD
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	870 lb (395 kg)
LOAD CAPACITY - WATER	670 lb (304 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	4
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	24 mph (39 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,680 lb (762 kg)
LENGTH (includes winch when standard)	119 in (3,023 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	77 in (1,956 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT117 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.88 psi (6.1 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	GREEN, BLACK, ORANGE

### AURORA 950 SX-R

HORSEPOWER	40HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	ACCESSORY
WINCH	ACCESSORY
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	STANDARD
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	850 lb (386 kg)
LOAD CAPACITY - WATER	650 lb (249 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	4
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	25 mph (40 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,700 lb (771 kg)
LENGTH (includes winch when standard)	119 in (3,023 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	77 in (1,956 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT117 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.88 psi (6.1 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	GREEN, BLACK, ORANGE



### AURORA 950 BIGFOOT MX8

HORSEPOWER	40HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	STANDARD
WINCH	3,500 lb
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	ACCESSORY
STRETCHER FRAME	ACCESSORY
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	1,060 lb (481 kg)
LOAD CAPACITY - WATER	860 lb (390 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	4
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	25 mph (40 Km/h)
SPEED - WATER	N/A
WEIGHT	1,490 lb (676 kg)
LENGTH (includes winch when standard)	126 in (3,200 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	XT119 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	N/A
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	BLACK



### CONQUEST 800 OUTFITTER 8X8

HORSEPOWER	30HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	LIQUID COOLED
ALTERNATOR OUTPUT (MAX)	60 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	STANDARD
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	STANDARD
WINCH	4,500 LB. WARN WINCH
FRONT RACK	STANDARD
BILGE PUMP	STANDARD
ROPS	N/A
STRETCHER FRAME	N/A
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	1,170 lb (531 kg)
LOAD CAPACITY - WATER	470 lb (213 kg)
TOWING CAPACITY	2,000 lb (907 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	2
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	17 mph (27 Km/h)
SPEED - WATER	N/A
WEIGHT	1,930 lb (875 kg)
LENGTH (includes winch when standard)	125 in (3,175 mm)
WIDTH	65 in (1,651 mm)
HEIGHT	53 in (1,346 mm)
AXLE BEARING EXTENSIONS	N/A
ENTRY STEP	DUAL REAR ENTRY STEPS
TIRES	ARGO XT119 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	1.06 psi (7.3 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	TRUETIMBER PRAIRIE CAMO



### CONQUEST 950 OUTFITTER 8X8

HORSEPOWER	40HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	STANDARD
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	STANDARD
WINCH	4,500 LB. WARN WINCH
FRONT RACK	STANDARD
BILGE PUMP	STANDARD
ROPS	N/A
STRETCHER FRAME	N/A
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	1,170 lb (531 kg)
LOAD CAPACITY - WATER	470 lb (213 kg)
TOWING CAPACITY	2,000 lb (907 kg)
SEATING CAPACITY - LAND	6
SEATING CAPACITY - WATER	2
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	17 mph (27 Km/h)
SPEED - WATER	N/A
WEIGHT	1,930 lb (875 kg)
LENGTH (includes winch when standard)	125 in (3,175 mm)
WIDTH	65 in (1,651 mm)
HEIGHT	53 in (1,346 mm)
AXLE BEARING EXTENSIONS	N/A
ENTRY STEP	DUAL REAR ENTRY STEPS
TIRES	ARGO XT119 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	1.06 psi (7.3 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	TRUETIMBER PRAIRIE CAMO

## CONQUEST SERIES SPECS



## XPLORER XC 90, XR 500 SERIES SPECS



### XPLORER XC 90

DISPLACEMENT	90CC
ENGINE STROKE	4-STROKE
CYLINDER ARRANGEMENT	SOHC SINGLE-CYLINDER
VALVE CONFIGURATION	2 VALVE
FUEL SYSTEM	CARBURETOR
COOLING SYSTEM	FAN
START METHOD	ELECTRIC START/KICK START
IGNITION	CDI
OVER RIDE BUTTON	N/A
TRANSMISSION TYPE	CVT AUTOMATIC
FINAL DRIVE	CHAIN DRIVE
DIFFERENTIAL FUNCTION	FRONT DIFFERENTIAL
DRIVE SYSTEM TYPE	2WD
ELECTRIC DIFF LOCK	N/A
GEAR SELECTION	F/N/R
REVERSE	YES
ENGINE BRAKING SYSTEM (EBS)	N/A
LENGTH	57 IN (1,448 MM)
WIDTH	36 IN (914 MM)
HEIGHT	37.9 IN (963 MM)
SEAT HEIGHT	25.5 IN (650 MM)
GROUND CLEARANCE	7.25 IN (184 MM)
WHEELBASE	37.9 IN (963 MM)
TOWING CAPACITY	N/A
DRY WEIGHT	260.1 LBS (118 KG)
WET WEIGHT	274.9 LBS (124.7 KG)
FUEL TANK CAPACITY	1.4 GAL (5.3 LTR)
RIDER CAPACITY	1
SUSPENSION - FRONT	INDEPENDENT SINGLE A-ARM
SUSPENSION - REAR	SWING ARM
SUSPENSION TRAVEL - FRONT	2.8 IN (71 MM)
SUSPENSION TRAVEL - REAR	2.9 IN (74 MM)
BRAKE - FRONT	DUAL DRUM
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT18X7-8
TIRE SIZE (REAR)	AT18X9-8
WHEEL RIM	STEEL
ELECTRIC POWER STEERING	NO
BATTERY	12V LEAD ACID
FRONT RACK	N/A
REAR RACK	N/A
FRONT BUMPER	STANDARD
HITCH	N/A
WINCH	N/A
HAND GUARD	N/A
12V CHARGER	N/A
SKID PLATE	PLASTIC
STORAGE	N/A
FRONT BRUSHGUARD	N/A
USB CHARGING PORT	N/A
REAR BOX STORAGE	N/A
INSTRUMENTATION	GEAR POSITION INDICATOR
LIGHTING	SINGLE 35W HI/LOW BEAM, SINGLE WITH BRAKE LIGHT
COLOR	WHITE



### XPLORER XR 500

DISPLACEMENT	443CC
ENGINE STROKE	4-STROKE
CYLINDER ARRANGEMENT	SOHC SINGLE-CYLINDER
VALVE CONFIGURATION	4 VALVE
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID
START METHOD	ELECTRIC START
IGNITION	ECU
OVER RIDE BUTTON	STANDARD
TRANSMISSION TYPE	CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT DIFFERENTIAL
DRIVE SYSTEM TYPE	2WD/ 4WD /LOCK
ELECTRIC DIFF LOCK	YES
GEAR SELECTION	H/L/N/R
REVERSE	YES
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	83.6 IN (2,123 MM)
WIDTH	43.4 IN (1,102 MM)
HEIGHT	46.9 IN (1,191 MM)
SEAT HEIGHT	33.2 IN (843 MM)
GROUND CLEARANCE	10.5 IN (267 MM)
WHEELBASE	47.9 IN (1,217 MM)
TOWING CAPACITY	1,050 LBS (477 KG)
DRY WEIGHT	604.0 LBS (274 KG)
WET WEIGHT	647.6 LBS (293.7 KG)
FUEL TANK CAPACITY	4.7 GAL (17.8 L)
RIDER CAPACITY	1
SUSPENSION - FRONT	INDEPENDENT DOUBLE A-ARM
SUSPENSION - REAR	INDEPENDENT DOUBLE A-ARM
SUSPENSION TRAVEL - FRONT	7 IN (180 MM)
SUSPENSION TRAVEL - REAR	7 IN (180 MM)
BRAKE - FRONT	DUAL HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT24x8-12 (KENDA)
TIRE SIZE (REAR)	AT24x10-12 (KENDA)
WHEEL RIM	STEEL
ELECTRIC POWER STEERING	NO
BATTERY	12V AGM
FRONT RACK	120 LB (54.5 KG)
REAR RACK	240 LB (109 KG)
FRONT BUMPER	STANDARD
HITCH	STANDARD/2" RECEIVER
WINCH	ACCESSORY
HAND GUARD	ACCESSORY
12V CHARGER	DC 12V 10A 120W
SKID PLATE	PLASTIC
STORAGE	N/A
FRONT BRUSHGUARD	N/A
USB CHARGING PORT	N/A
REAR BOX STORAGE	N/A
INSTRUMENTATION	DIGITAL INSTRUMENT PANEL
LIGHTING	DUAL 8W HI/LOW BEAM, SINGLE WITH BRAKE LIGHT
COLOR	RED OR GREEN



### XPLORER XR 500 SE

DISPLACEMENT	443CC
ENGINE STROKE	4-STROKE
CYLINDER ARRANGEMENT	SOHC SINGLE-CYLINDER
VALVE CONFIGURATION	4 VALVE
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID
START METHOD	ELECTRIC START
IGNITION	ECU
OVER RIDE BUTTON	STANDARD
TRANSMISSION TYPE	CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT DIFFERENTIAL
DRIVE SYSTEM TYPE	2WD/ 4WD /LOCK
ELECTRIC DIFF LOCK	YES
GEAR SELECTION	H/L/N/R
REVERSE	YES
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	83.6 IN (2,123 MM)
WIDTH	43.4 IN (1,102 MM)
HEIGHT	46.9 IN (1,191 MM)
SEAT HEIGHT	33.2 IN (843 MM)
GROUND CLEARANCE	10.5 IN (267 MM)
WHEELBASE	47.9 IN (1,217 MM)
TOWING CAPACITY	1,050 LBS (477 KG)
DRY WEIGHT	627.0 LBS (284 KG)
WET WEIGHT	670 LBS (304 KG)
FUEL TANK CAPACITY	4.7 GAL (17.8 L)
RIDER CAPACITY	1
SUSPENSION - FRONT	INDEPENDENT DOUBLE A-ARM
SUSPENSION - REAR	INDEPENDENT DOUBLE A-ARM
SUSPENSION TRAVEL - FRONT	7 IN (180 MM)
SUSPENSION TRAVEL - REAR	7 IN (180 MM)
BRAKE - FRONT	DUAL HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT24x8-12 (KENDA)
TIRE SIZE (REAR)	AT24x10-12 (KENDA)
WHEEL RIM	ALUMINUM
ELECTRIC POWER STEERING	NO
BATTERY	12V AGM
FRONT RACK	120 LB (54.5 KG)
REAR RACK	240 LB (109 KG)
FRONT BUMPER	STANDARD
HITCH	STANDARD/2" RECEIVER
WINCH	3,000 LB WINCH
HAND GUARD	ACCESSORY
12V CHARGER	DC 12V 10A 120W
SKID PLATE	PLASTIC
STORAGE	N/A
FRONT BRUSHGUARD	N/A
USB CHARGING PORT	N/A
REAR BOX STORAGE	N/A
INSTRUMENTATION	DIGITAL INSTRUMENT PANEL
LIGHTING	DUAL 8W HI/LOW BEAM, SINGLE WITH BRAKE LIGHT
COLOR	PAINTED FLAME ORANGE OR PAINTED SLATE GREY



### XPLORER XR 700 EPS

DISPLACEMENT	695CC
ENGINE STROKE	4-STROKE
CYLINDER ARRANGEMENT	SOHC SINGLE-CYLINDER
VALVE CONFIGURATION	4 VALVE
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID
START METHOD	ELECTRIC START
IGNITION	ECU
OVER RIDE BUTTON	N/A
TRANSMISSION TYPE	CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT DIFFERENTIAL
DRIVE SYSTEM TYPE	2WD/ 4WD /LOCK
ELECTRIC DIFF LOCK	YES
GEAR SELECTION	H/L/N/R/P
REVERSE	YES
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	87 IN (2,210 CMM)
WIDTH	48 IN (1,220 MM)
HEIGHT	48.4 IN (1,229 MM)
SEAT HEIGHT	34.6 IN (880 MM)
GROUND CLEARANCE	10.8 IN (274 MM)
WHEELBASE	51.1 IN (1,298 MM)
TOWING CAPACITY	1,050 LBS (477 KG)
DRY WEIGHT	736.3 LBS (334 KG)
WET WEIGHT	785.3 LBS (356.2 KG)
FUEL TANK CAPACITY	5.5 GAL (20.8 L)
RIDER CAPACITY	1
SUSPENSION - FRONT	INDEPENDENT DOUBLE A-ARM
SUSPENSION - REAR	INDEPENDENT DOUBLE A-ARM W SWAY BAR
SUSPENSION TRAVEL - FRONT	7 IN (180 MM)
SUSPENSION TRAVEL - REAR	7.4 IN (188 MM)
BRAKE - FRONT	DUAL HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT25X8-12 (MAXXIS)
TIRE SIZE (REAR)	AT25X10-12 (MAXXIS)
WHEEL RIM	STEEL
ELECTRIC POWER STEERING	YES
BATTERY	12V AGM
FRONT RACK	120 LB (54.5 KG)
REAR RACK	240 LB (109 KG)
FRONT BUMPER	N/A
HITCH	STANDARD/2" RECEIVER
WINCH	3,000 LB WINCH
HAND GUARD	ACCESSORY
12V CHARGER	DC 12V 10A 120W
SKID PLATE	PLASTIC
STORAGE	LOCKABLE FRONT FENDER AND CENTER CONSOLE
FRONT BRUSHGUARD	ACCESSORY
USB CHARGING PORT	STANDARD
REAR BOX STORAGE	N/A
INSTRUMENTATION	DIGITAL INSTRUMENT PANEL
LIGHTING	DUAL 35W HI/LOW BEAM, DUAL WITH BRAKE LIGHT
COLOR	RED OR GREEN



### XPLORER XR 700 LE

DISPLACEMENT	695CC
ENGINE STROKE	4-STROKE
CYLINDER ARRANGEMENT	SOHC SINGLE-CYLINDER
VALVE CONFIGURATION	4 VALVE
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID
START METHOD	ELECTRIC START
IGNITION	ECU
OVER RIDE BUTTON	N/A
TRANSMISSION TYPE	CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT DIFFERENTIAL
DRIVE SYSTEM TYPE	2WD/ 4WD /LOCK
ELECTRIC DIFF LOCK	YES
GEAR SELECTION	H/L/N/R/P
REVERSE	YES
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	87 IN (2,210 MM)
WIDTH	48 IN (1,220 MM)
HEIGHT	48.4 IN (1,229 MM)
SEAT HEIGHT	34.6 IN (880 MM)
GROUND CLEARANCE	10.8 IN (274 MM)
WHEELBASE	51.1 IN (1,298 MM)
TOWING CAPACITY	1,050 LBS (477 KG)
DRY WEIGHT	759 LBS (344 KG)
WET WEIGHT	808 LBS (367 KG)
FUEL TANK CAPACITY	5.5 GAL (20.8 L)
RIDER CAPACITY	1
SUSPENSION - FRONT	INDEPENDENT DOUBLE A-ARM
SUSPENSION - REAR	INDEPENDENT DOUBLE A-ARM W SWAY BAR
SUSPENSION TRAVEL - FRONT	7 IN (180 MM)
SUSPENSION TRAVEL - REAR	7.4 IN (188 MM)
BRAKE - FRONT	DUAL HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT26X8-14 (MAXXIS)
TIRE SIZE (REAR)	AT26X10-14 (MAXXIS)
WHEEL RIM	ALUMINUM
ELECTRIC POWER STEERING	YES
BATTERY	12V AGM
FRONT RACK	120 LB (54.5 KG)
REAR RACK	240 LB (109 KG)
FRONT BUMPER	N/A
HITCH	STANDARD/2" RECEIVER
WINCH	3,000 LB WINCH
HAND GUARD	STANDARD
12V CHARGER	DC 12V 10A 120W
SKID PLATE	PLASTIC
STORAGE	LOCKABLE FRONT FENDER AND CENTER CONSOLE
FRONT BRUSHGUARD	ACCESSORY
USB CHARGING PORT	STANDARD
REAR BOX STORAGE	N/A
INSTRUMENTATION	DIGITAL INSTRUMENT PANEL
LIGHTING	DUAL 35W HI/LOW BEAM, DUAL WITH BRAKE LIGHT
COLOR	PAINTED FLAME ORANGE OR PAINTED SLATE GREY

## XPLORER XR 700 SERIES SPECS



## XPLORER XRT SERIES SPECS



### XPLORER XRT 570

DISPLACEMENT	561.4CC
ENGINE STROKE	4-STROKE
CYLINDER ARRANGEMENT	SOHC SINGLE CYLINDER
VALVE CONFIGURATION	4 VALVE
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID
START METHOD	ELECTRIC START
IGNITION	ECU
OVER RIDE BUTTON	YES
TRANSMISSION TYPE	V BELT CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT & REAR DIFFERENTIAL
DRIVE SYSTEM TYPE	2WD/4WD/LOCK
ELECTRIC DIFF LOCK	YES
GEAR SELECTION	L/H/N/R/P
REVERSE	YES
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	89.8 IN (2,280 MM)
WIDTH	48.4 IN (1,229 MM)
HEIGHT	55.9 IN (1,420 MM)
SEAT HEIGHT	36.1 IN (916 MM)
GROUND CLEARANCE	12.6 IN (320 MM)
WHEELBASE	57.1 IN (1,450 MM)
TOWING CAPACITY	1,225 LB (557 KG)
DRY WEIGHT	851 LB (387 KG)
WET WEIGHT	987.7 LB (448KG)
FUEL TANK CAPACITY	4.2 GAL (16 L)
RIDER CAPACITY	2
SUSPENSION - FRONT	INDEPENDENT DOUBLE A-ARM
SUSPENSION - REAR	INDEPENDENT DOUBLE A-ARM
SUSPENSION TRAVEL - FRONT	8.7 IN (220 MM)
SUSPENSION TRAVEL - REAR	9.4 IN (239 MM)
BRAKE - FRONT	HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT25X8-12 (KENDA)
TIRE SIZE (REAR)	AT25X10-12 (KENDA)
WHEEL RIM	STEEL
ELECTRIC POWER STEERING	NO
BATTERY	12V AGM
FRONT RACK	99 LB (45 KG)
REAR RACK	165 LB (75 KG)
FRONT BUMPER	N/A
HITCH	STANDARD/2" RECEIVER
WINCH	ACCESSORY
HAND GUARD	NO
12V CHARGER	DC 12V 10A 120W X2
SKID PLATE	PLASTIC
STORAGE	N/A
FRONT BRUSHGUARD	N/A
USB CHARGING PORT	N/A
REAR BOX STORAGE	N/A
INSTRUMENTATION	DIGITAL INSTRUMENT PANEL
LIGHTING	DUAL 60W HI/LOW BEAM LIGHTS, DUAL BRAKELIGHTS, TAILLIGHTS
COLOR	RED



### XPLORER XRT 570 LE

DISPLACEMENT	561.4CC
ENGINE STROKE	4-STROKE
CYLINDER ARRANGEMENT	SOHC SINGLE CYLINDER
VALVE CONFIGURATION	4 VALVE
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID
START METHOD	ELECTRIC START
IGNITION	ECU
OVER RIDE BUTTON	YES
TRANSMISSION TYPE	V BELT CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT & REAR DIFFERENTIAL
DRIVE SYSTEM TYPE	2WD/4WD/LOCK
ELECTRIC DIFF LOCK	YES
GEAR SELECTION	L/H/N/R/P
REVERSE	YES
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	89.8 IN (2,280 MM)
WIDTH	48.4 IN (1,229 MM)
HEIGHT	55.9 IN (1,420 MM)
SEAT HEIGHT	36.1 IN (916 MM)
GROUND CLEARANCE	12.6 IN (320 MM)
WHEELBASE	57.1 IN (1,450 MM)
TOWING CAPACITY	1,225 LB (557 KG)
DRY WEIGHT	874 LB (396 KG)
WET WEIGHT	1,010 LB (458KG)
FUEL TANK CAPACITY	4.2 GAL (16 L)
RIDER CAPACITY	2
SUSPENSION - FRONT	INDEPENDENT DOUBLE A-ARM
SUSPENSION - REAR	INDEPENDENT DOUBLE A-ARM
SUSPENSION TRAVEL - FRONT	8.7 IN (220 MM)
SUSPENSION TRAVEL - REAR	9.4 IN (239 MM)
BRAKE - FRONT	HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT26X8-14 (MAXXIS)
TIRE SIZE (REAR)	AT26X10-14 (MAXXIS)
WHEEL RIM	ALUMINUM
ELECTRIC POWER STEERING	YES
BATTERY	12V AGM
FRONT RACK	99 LB (45 KG)
REAR RACK	165 LB (75 KG)
FRONT BUMPER	N/A
HITCH	STANDARD/2" RECEIVER
WINCH	3,000 LB WINCH
HAND GUARD	NO
12V CHARGER	DC 12V 10A 120W X2
SKID PLATE	PLASTIC
STORAGE	N/A
FRONT BRUSHGUARD	STANDARD
USB CHARGING PORT	N/A
REAR BOX STORAGE	N/A
INSTRUMENTATION	DIGITAL INSTRUMENT PANEL
LIGHTING	DUAL 60W HI/LOW BEAM LIGHTS, DUAL BRAKELIGHTS, TAILLIGHTS
COLOR	PAINTED GRAPHITE METALLIC



### XPLORER XRT 1000 LE

DISPLACEMENT	997CC
ENGINE STROKE	4-STROKE
CYLINDER ARRANGEMENT	SOHC TWIN CYLINDER
VALVE CONFIGURATION	4 VALVE
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID
START METHOD	ELECTRIC START
IGNITION	ECU
OVER RIDE BUTTON	YES
TRANSMISSION TYPE	CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT & REAR DIFFERENTIAL
DRIVE SYSTEM TYPE	2WD/4WD/LOCK
ELECTRIC DIFF LOCK	YES
GEAR SELECTION	L/H/N/R/P
REVERSE	YES
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	92.1 IN (2,340 MM)
WIDTH	49.4 IN (1,255 MM)
HEIGHT	49.8 IN (1,265 MM)
SEAT HEIGHT	36.1 IN (916 MM)
GROUND CLEARANCE	11.6 IN (295 MM)
WHEELBASE	56.9 IN (1,450 MM)
TOWING CAPACITY	1,300 LB (590 KG)
DRY WEIGHT	1,080 LB (490 KG)
WET WEIGHT	1,124 LBS (510 KG)
FUEL TANK CAPACITY	6.1 GAL (23 L)
RIDER CAPACITY	2
SUSPENSION - FRONT	INDEPENDENT DOUBLE A-ARM
SUSPENSION - REAR	INDEPENDENT DOUBLE A-ARM
SUSPENSION TRAVEL - FRONT	8.7 IN (220 MM)
SUSPENSION TRAVEL - REAR	9.3 IN (236 MM)
BRAKE - FRONT	HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT26X8-14 (MAXXIS)
TIRE SIZE (REAR)	AT26X10-14 (MAXXIS)
WHEEL RIM	ALUMINUM
ELECTRIC POWER STEERING	YES
BATTERY	12V AGM
FRONT RACK	99 LB (45 KG)
REAR RACK	165 LB (75 KG)
FRONT BUMPER	YES
HITCH	STANDARD/2" RECEIVER
WINCH	3,000 LB WINCH
HAND GUARD	YES
12V CHARGER	DC 12V 10A 120W X2
SKID PLATE	PLASTIC
STORAGE	N/A
FRONT BRUSHGUARD	ACCESSORY
USB CHARGING PORT	N/A
REAR BOX STORAGE	N/A
INSTRUMENTATION	DIGITAL INSTRUMENT PANEL
LIGHTING	DUAL 60W HI/LOW BEAM LIGHTS, DUAL BRAKELIGHTS, TAILLIGHTS
COLOR	PAINTED GRAPHITE METALLIC



### MAGNUM XF 500

DISPLACEMENT	443CC
ENGINE STROKE	4-STROKE
CYLINDER ARRANGEMENT	SOHC SINGLE-CYLINDER
VALVE CONFIGURATION	4 VALVE
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID
START METHOD	ELECTRIC START
IGNITION	ECU
OVER RIDE BUTTON	N/A
TRANSMISSION TYPE	CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT DIFFERENTIAL
DRIVE SYSTEM TYPE	2WD/ 4WD /LOCK
ELECTRIC DIFF LOCK	YES
GEAR SELECTION	H/L/N/R/P
REVERSE	YES
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	106.6 IN (2,700 MM)
WIDTH	56.7 IN (1,440 MM)
HEIGHT	72.8 IN (1,849 MM)
SEAT HEIGHT	N/A
GROUND CLEARANCE	10 IN (254 MM)
WHEELBASE	72 IN (1,829 MM)
TOWING CAPACITY	1,200 LBS (544 KG)
DRY WEIGHT	1,080 LBS (490 KG)
WET WEIGHT	1,148 LBS (520.7 KG)
FUEL TANK CAPACITY	8.5 GAL (32 L)
RIDER CAPACITY	2
SUSPENSION - FRONT	INDEPENDENT DOUBLE A-ARM
SUSPENSION - REAR	INDEPENDENT DOUBLE A-ARM
SUSPENSION TRAVEL - FRONT	7.5 IN (190 MM)
SUSPENSION TRAVEL - REAR	7.5 IN (190 MM)
BRAKE - FRONT	DUAL HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT25X8-12 (MAXXIS)
TIRE SIZE (REAR)	AT25X10-12 (MAXXIS)
WHEEL RIM	STEEL
ELECTRIC POWER STEERING	NO
BATTERY	12V AGM
FRONT RACK	N/A
REAR RACK	N/A
FRONT BUMPER	N/A
HITCH	STANDARD/2" RECEIVER
WINCH	ACCESSORY
HAND GUARD	N/A
12V CHARGER	STANDARD
SKID PLATE	PLASTIC
STORAGE	UNDERHOOD, UNDERSEAT, TAILGATE, GLOVE BOX
FRONT BRUSHGUARD	N/A
USB CHARGING PORT	N/A
REAR BOX STORAGE	500 LB (227.3 KG)
INSTRUMENTATION	DIGITAL INSTRUMENT PANEL
LIGHTING	DUAL 8W HI/LOW BEAM, DUAL WITH BRAKE LIGHT
COLOR	GREEN



### MAGNUM XF 500 LE

DISPLACEMENT	443CC
ENGINE STROKE	4-STROKE
CYLINDER ARRANGEMENT	SOHC SINGLE-CYLINDER
VALVE CONFIGURATION	4 VALVE
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID
START METHOD	ELECTRIC START
IGNITION	ECU
OVER RIDE BUTTON	N/A
TRANSMISSION TYPE	CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT DIFFERENTIAL
DRIVE SYSTEM TYPE	2WD/ 4WD /LOCK
ELECTRIC DIFF LOCK	YES
GEAR SELECTION	H/L/N/R/P
REVERSE	YES
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	106.6 IN (2,700 MM)
WIDTH	56.7 IN (1,440 MM)
HEIGHT	72.8 IN (1,849 MM)
SEAT HEIGHT	N/A
GROUND CLEARANCE	10 IN (254 MM)
WHEELBASE	72 IN (1,829 MM)
TOWING CAPACITY	1,200 LBS (544 KG)
DRY WEIGHT	1,103 LBS (500 KG)
WET WEIGHT	1,171 LBS (531 KG)
FUEL TANK CAPACITY	8.5 GAL (32 L)
RIDER CAPACITY	2
SUSPENSION - FRONT	INDEPENDENT DOUBLE A-ARM
SUSPENSION - REAR	INDEPENDENT DOUBLE A-ARM
SUSPENSION TRAVEL - FRONT	7.5 IN (190 MM)
SUSPENSION TRAVEL - REAR	7.5 IN (190 MM)
BRAKE - FRONT	DUAL HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT25X8-12 (DURO)
TIRE SIZE (REAR)	AT25X10-12 (DURO)
WHEEL RIM	ALUMINUM
ELECTRIC POWER STEERING	YES
BATTERY	12V AGM
FRONT RACK	N/A
REAR RACK	N/A
FRONT BUMPER	N/A
HITCH	STANDARD/2" RECEIVER
WINCH	3,000 LB WINCH
HAND GUARD	N/A
12V CHARGER	STANDARD
SKID PLATE	PLASTIC
STORAGE	UNDERHOOD, UNDERSEAT, TAILGATE, GLOVE BOX
FRONT BRUSHGUARD	N/A
USB CHARGING PORT	N/A
REAR BOX STORAGE	500 LB (227.3 KG)
INSTRUMENTATION	DIGITAL INSTRUMENT PANEL
LIGHTING	DUAL 8W HI/LOW BEAM, DUAL WITH BRAKE LIGHT
COLOR	PAINTED FLAME ORANGE OR PLANTED SLATE GREY

## SIDE X SIDE SPECS



## AURORA RESPONDER SPECS



### AURORA 850 SX RESPONDER 8X8

HORSEPOWER	33HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	STANDARD
WINCH	3,500 lb
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	ACCESSORY
STRETCHER FRAME	STANDARD
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	960 lb (436 kg)
LOAD CAPACITY - WATER	760 lb (345 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	4
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	24 mph (39 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,590 lb (723 kg)
LENGTH (includes winch when standard)	126 in (3,200 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	51 in (1,295 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT119 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.67 psi (4.6 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	RED, ORANGE

### AURORA 850 SX-R RESPONDER 8X8

HORSEPOWER	33HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	FAN COOLED
ALTERNATOR OUTPUT (MAX)	50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	ACCESSORY
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL W/APS
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	STANDARD
WINCH	3,500 lb
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	STANDARD
STRETCHER FRAME	STANDARD
REAR MESH	N/A
ROOF	N/A
POWER DUMP BOX	N/A
LOAD CAPACITY - LAND	730 lb (331 kg)
LOAD CAPACITY - WATER	530 lb (240 kg)
TOWING CAPACITY	1,800 lb (816 kg)
SEATING CAPACITY - LAND	4
SEATING CAPACITY - WATER	4
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	24 mph (39 Km/h)
SPEED - WATER	3 mph (5 Km/h)
WEIGHT	1,820 lb (825 kg)
LENGTH (includes winch when standard)	126 in (3,200 mm)
WIDTH	60 in (1,524 mm)
HEIGHT	77 in (1,956 mm)
AXLE BEARING EXTENSIONS	STANDARD
ENTRY STEP	ACCESSORY
TIRES	ARGO XT119 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	0.67 psi (4.6 kPa)
GROUND CLEARANCE (TIRES)	10 in (254 mm)
GROUND CLEARANCE (TRACKS)	11 in (279 mm)
WARRANTY	1 YEAR
COLORS	RED, ORANGE

## CONQUEST PRO SERIES SPECS



### CONQUEST PRO 800|950 XT

HORSEPOWER	30HP   40HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	LIQUID COOLED   FAN COOLED
ALTERNATOR OUTPUT (MAX)	60 AMPS   50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	STANDARD
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	STANDARD
WINCH	4,500 LB. WARN WINCH
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	ACCESSORY
STRETCHER FRAME	N/A
REAR MESH	ACCESSORY
ROOF	ACCESSORY
POWER DUMP BOX	ACCESSORY
LOAD CAPACITY - LAND	1,210 lb (549 kg)
LOAD CAPACITY - WATER	510 lb (231 kg)
TOWING CAPACITY	2,000 lb (907 kg)
SEATING CAPACITY - LAND	2
SEATING CAPACITY - WATER	2
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	17 mph (27 Km/h)
SPEED - WATER	N/A
WEIGHT	1,890 lb (857 kg)
LENGTH (includes winch when standard)	125 in (3,175 mm)
WIDTH	65 in (1,651 mm)
HEIGHT	49 in (1,245 mm)
AXLE BEARING EXTENSIONS	N/A
ENTRY STEP	ACCESSORY
TIRES	ARGO XT119 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	1.06 psi (7.3 kPa)
GROUND CLEARANCE (TIRES)	9 in (228 mm)
GROUND CLEARANCE (TRACKS)	10 in (254 mm)
WARRANTY	1 YEAR
COLORS	GREEN/BLACK/INDUSTRIAL YELLOW

### CONQUEST PRO 800|950 XT-L

HORSEPOWER	30HP   40HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	LIQUID COOLED   FAN COOLED
ALTERNATOR OUTPUT (MAX)	60 AMPS   50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	STANDARD
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	STANDARD
WINCH	4,500 LB. WARN WINCH
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	STANDARD
STRETCHER FRAME	N/A
REAR MESH	STANDARD
ROOF	STANDARD
POWER DUMP BOX	ACCESSORY
LOAD CAPACITY - LAND	1,048 lb (475 kg)
LOAD CAPACITY - WATER	NOT AMPHIBIOUS
TOWING CAPACITY	2,000 lb (907 kg)
SEATING CAPACITY - LAND	2
SEATING CAPACITY - WATER	N/A
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	17 mph (27 Km/h)
SPEED - WATER	N/A
WEIGHT	2,052 lb (931 kg)
LENGTH (includes winch when standard)	125 in (3,175 mm)
WIDTH	65 in (1,651 mm)
HEIGHT	80.5 in (2,045 mm)
AXLE BEARING EXTENSIONS	N/A
ENTRY STEP	ACCESSORY
TIRES	ARGO XT119 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	1.06 psi (7.3 kPa)
GROUND CLEARANCE (TIRES)	9 in (228 mm)
GROUND CLEARANCE (TRACKS)	10 in (254 mm)
WARRANTY	1 YEAR
COLORS	GREEN/INDUSTRIAL YELLOW

### CONQUEST PRO 800|950 XT-X

HORSEPOWER	30HP   40HP
CYLINDER	V-TWIN
FUEL SYSTEM	EFI
COOLING	LIQUID COOLED   FAN COOLED
ALTERNATOR OUTPUT (MAX)	60 AMPS   50 AMPS
SERVICE BRAKES	HYDRAULIC
STEERING BRAKES	HYDRAULIC
AUTO CHAIN LUBRICATION	STANDARD
BRAKE COOLING FAN	ACCESSORY
TRANSMISSION	ADMIRAL
DRIVE BELT	HEAVY DUTY
FULL SKID PLATE	STANDARD
BRUSHGUARD	STANDARD
WINCH	4,500 LB. WARN WINCH
FRONT RACK	ACCESSORY
BILGE PUMP	STANDARD
ROPS	STANDARD
STRETCHER FRAME	N/A
REAR MESH	STANDARD
ROOF	STANDARD
POWER DUMP BOX	STANDARD
LOAD CAPACITY - LAND	848 lb (385 kg)
LOAD CAPACITY - WATER	NOT AMPHIBIOUS
TOWING CAPACITY	2,000 lb (907 kg)
SEATING CAPACITY - LAND	2
SEATING CAPACITY - WATER	N/A
FUEL CAPACITY	8.5 gal (32 L)
SPEED - LAND	17 mph (27 Km/h)
SPEED - WATER	N/A
WEIGHT	2,252 lb (1,021 kg)
LENGTH (includes winch when standard)	125 in (3,175 mm)
WIDTH	65 in (1,651 mm)
HEIGHT	80.5 in (2,045 mm)
AXLE BEARING EXTENSIONS	N/A
ENTRY STEP	ACCESSORY
TIRES	ARGO XT119 25X12-9
RIMS	STEEL AIRLOCK
GROUND PRESSURE (18" RUBBER TRACKS)	1.06 psi (7.3 kPa)
GROUND CLEARANCE (TIRES)	9 in (228 mm)
GROUND CLEARANCE (TRACKS)	10 in (254 mm)
WARRANTY	1 YEAR
COLORS	GREEN/INDUSTRIAL YELLOW



**ARGO Sherp PRO XT SPECS**



**ARGO Sherp PRO XT**

ENGINE MAKE	DOOSAN
DISPLACEMENT	1.8 L
FUEL TYPE	DIESEL
CYLINDER	3
EMISSION STANDARDS	EPA, STAGE 5/TIER 4 FINAL
DOC	DOC+DPF/DOC ONLY
COOLING SYSTEM	LIQUID
HORSEPOWER - MAX	55 HP (41 kW)
TORQUE - MAX	190 NM
FUEL CONSUMPTION	1.3 - 2.2 GAL/H (5-8 LPH)
VOLTAGE	12 V
ALTERNATOR CAPACITY	140 AMP
STARTING	ELECTRIC
BATTERY TYPE - MAIN/BACKUP	LEAD ACID
TRANSMISSION TYPE	6-SPEED MANUAL
FINAL DRIVE	ENCLOSED CHAINS IN OIL BATH
STEERING	TWO LEVER HYDRAULIC SKID STEERING
PAYLOAD	2,645 LBS (1,200 KG)
PEOPLE CAPACITY	UP TO 8
MAX CLIMB/DESCEND GRADE	35 DEGREES
MAX SIDEHILL GRADE	30 DEGREES
OVERALL LENGTH	157" (3,988 MM)
OVERALL WIDTH	101" (2,570 MM)
OVERALL HEIGHT	118" (2,846 MM)
GROUND CLEARANCE	26" (660 MM)
WHEELBASE	86" (2,200 MM)
TOWING CAPACITY	5,180 LBS (2,350 KG) FRONT/REAR
TONGUE WEIGHT	330 LBS (150 KG) FRONT/REAR
DRY WEIGHT	5,291 LBS (2,400 KG)
FUEL TANK CAPACITY	25 GAL (95 L)

AUXILIARY FUEL CAPACITY	UP TO 61.2 GAL (231.6 L) 15.3 GAL (57.9 L) CAPACITY WHEEL CANISTER X4
INTERIOR VOLUME - OVERALL	275.5 FT3 (7.8 M3)
INTERIOR VOLUME - FRONT	70.5 FT3 (2.0 M3)
INTERIOR VOLUME - REAR	205 FT3 (5.8 M3)
SPEED - LAND	25 MPH (40 KM/H)
SPEED - WATER	4 MPH (6 KM/H)
SUSPENSION	ADJUSTABLE PNEUMATIC CIRCULATING TIRES
BRAKES	HYDRAULIC DUAL CALIPER/DUAL DISC
PARKING BRAKES	HANDBRAKE
TIRE SIZE	71X23-25 (TUBELESS, ULTRA-LOW PRESSURE)
WHEELS	STEEL BEADLOCK
GROUND PRESSURE	0.9 - 2.1 PSI (0.07 - 0.15 KG/CM2)
PRESSURE CONTROL	ADJUSTABLE BY EXHAUST GAS
ROPS (CERTIFICATION)	FULL ROPS (ISO 3471)
FRONT SEATS - 2 FRONT FACING	STANDARD WITH 3 POINT SEATBELTS
REAR SEATS - 2 FRONT FACING	OPTIONAL
REAR SEATS - 4 FRONT FACING	OPTIONAL
REAR SEATS - 6 SIDE FACING	OPTIONAL
INSTRUMENTATION CONTROL	MULTIFUNCTIONAL DIGITAL DISPLAY
REVIEW CAMERA	STANDARD
HEATER	STANDARD
AIR CONDITIONER	STANDARD
HEADLIGHTS	LED - HI/LOW BEAM
BUMPERS	FRONT AND REAR
HITCH	2" RECEIVER - FRONT AND REAR
WINCH	OPTIONAL 9,000 LB
BILGE PUMP	STANDARD
STORAGE - GLOVE & UNDER FLOOR	STANDARD
MIRRORS	STANDARD
COLOR	BLACK OR WHITE

**ARGO Sherp ARK SPECS**



**ARGO Sherp ARK XTX|XTZ**

ENGINE MAKE	DOOSAN
DISPLACEMENT	2.4 L
FUEL TYPE	DIESEL
CYLINDER	4
EMISSION STANDARDS	EPA, STAGE 5/TIER 4 FINAL
DOC	DOC+DPF/DOC ONLY
COOLING SYSTEM	LIQUID
HORSEPOWER - MAX	74 HP (55 kW)
TORQUE - MAX	320 NM
FUEL CONSUMPTION	2 - 3 GAL/H (8-12 LPH)
VOLTAGE	12 V
ALTERNATOR CAPACITY	140 AMP
STARTING	ELECTRIC
BATTERY TYPE - MAIN/BACKUP	LEAD ACID
TRANSMISSION TYPE	5-SPEED MANUAL
FINAL DRIVE	ENCLOSED CHAINS IN OIL BATH
STEERING	STEERING WHEEL, MULTI-POWER ARTICULATED (3 AXIS)
PAYLOAD XTX	7,500 LBS (3,400 KG) [882 LBS (400 KG) FRONT/6,614 LBS (3,000 KG) REAR]
PAYLOAD XTZ	4,409 LBS (2,000 KG) Total [882 LBS (400 KG) FRONT / 3,527 LBS (1,600 KG) REAR]
PEOPLE CAPACITY XTX/XTZ	UP TO 4   UP TO 22 (4-FRONT/18-REAR)
MAX CLIMB/DESCEND GRADE	40 DEGREES
MAX SIDEHILL GRADE	30 DEGREES
OVERALL LENGTH	380" (9,632 MM)
OVERALL WIDTH	100" (2,520 MM)
OVERALL HEIGHT XTX/XTZ	102" (2,605 MM)   114" (2,900 MM)
GROUND CLEARANCE	24" (600 MM)
WHEELBASE XTX/XTZ	FRONT 77" (1,962 MM) / REAR 65" (1,655 MM) / 64" (1,637 MM)
TOWING CAPACITY	8,818 LBS (4,000 KG)
TONGUE WEIGHT	330 LBS (150 KG) FRONT ONLY ON POWER UNIT
DRY WEIGHT XTX/XTZ	9,480 LBS (4,300 KG)   11,865 LBS (5,382 KG)
FUEL TANK CAPACITY	48 GAL (181.7 L): 8 GAL (30 L) FRONT/ 40 GAL (150 L) REAR

AUXILIARY FUEL CAPACITY	UP TO 153 GAL (579.1 L) 15.3 GAL (57.9 L) CAPACITY WHEEL CANISTER X10
INTERIOR VOLUME - OVERALL XTX/XTZ	218 FT3 (9M3)   710 FT3 (20.1M3)
INTERIOR VOLUME - FRONT	208 FT3 (5.9 M3)
INTERIOR VOLUME - REAR XTX/XTZ	109.5 FT3 (3.1 M3)   501.5 FT3 (14.2 M3)
SPEED - LAND	18 MPH (30KM/H)
SPEED - WATER	4 MPH (6 KM/H)
SUSPENSION	ADJUSTABLE PNEUMATIC CIRCULATING TIRES
BRAKES	HYD CALIPER DISC
PARKING BRAKES	HANDBRAKE
TIRE SIZE	63X23-25 (TUBELESS, ULTRA-LOW PRESSURE)
WHEELS	STEEL BEADLOCK
GROUND PRESSURE	0.9 - 2.1 PSI (0.07 - 0.15 KG/CM2)
PRESSURE CONTROL	ADJUSTABLE BY EXHAUST GAS
ROPS (CERTIFICATION)	FULL ROPS (ISO 3471)
FRONT SEATS - 2 FRONT FACING	STANDARD WITH 3 POINT SEATBELTS
REAR SEATS - 2 FRONT FACING	STANDARD WITH 3 POINT SEATBELTS
REAR SEATS - 4 FRONT FACING	N/A
REAR SEATS - 6 SIDE FACING	N/A
INSTRUMENTATION CONTROL	MULTIFUNCTIONAL DIGITAL DISPLAY
REVIEW CAMERA	STANDARD
HEATER	STANDARD
AIR CONDITIONER	N/A
HEADLIGHTS	LED - HI/LOW BEAM
BUMPERS	FRONT
HITCH	2" RECEIVER - FRONT
WINCH	N/A
BILGE PUMP	STANDARD
STORAGE - GLOVE & UNDER FLOOR	STANDARD
MIRRORS	STANDARD
COLOR	BLACK



## A STRONG FAMILY.

Our new '22 lineup is the result of everyone at ARGO working hard together to deliver our brand promise to our dealers and customers — *Know no boundaries*. Our full lineup of incredible XTVs, ATVs, SXSs, UTVs and UGVs provides an opportunity to go where others can't.







**GO**  
ANYWHERE™

**ARGOxtv.COM**

*Some vehicle applications shown are for demonstration purposes, originating from third parties and not available from ARGO. In all cases vehicle load limits have been considered. Never overload your ARGO vehicle. Always remain seated while in your ARGO vehicle. ARGO vehicles can be hazardous to operate. Improper use can cause severe injury or death. Riders must wear an approved helmet, eye protection, protective clothing and, when operating in water, always wear a properly-fitted personal flotation device. Use handholds and stay completely inside the vehicle. Each rider must read and understand the operator's manual before riding. Follow all instructions and warnings. Avoid abrupt maneuvers, paved surfaces, hard acceleration when turning, and side hilling; slow down before entering a turn. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Never carry a passenger on a single-rider ATV. XR AND XRT ATV models are for users over 16 years old only. XC 90 youth model is only for kids 12 and up. Never operate on public roads. ARGO vehicles are designated for off-highway use only — collisions with cars and trucks can occur. Never drive or ride under the influence of alcohol or drugs. Do not shoot from or lean firearms or bows against ARGO vehicles. ARGO recommends that all riders take an approved ATV or UTV training course. When equipped with tracks, Conquest Pro-Series models are not fully amphibious, however water crossing is possible with a fording depth of 26" (660 mm). For safety or training information in the U.S., call the ATV Safety Institute at (800) 887-2887. In Canada, please contact the Canada Safety Council at (613) 739-1535 or see your dealer. Along with concerned conservationists everywhere, ARGO urges you to respect public and private lands. Ride only on designated areas or trails. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when riding. All materials and specifications are subject to change without notice. All specifications, claims and information contained within are based on current knowledge and readily available as printed material as of July 31, 2021.*

*ARGO, Frontier, Aurora, Conquest, Xplorer, Magnum, XTV, and AirLock are trademarks of Ontario Drive and Gear Limited.*

**PART#: 095-0016** Printed in Canada 07/2021